

Datasheet of LTCC Device

RoHS & Halogen Free & REACH Compliance

Laminated Ceramic Coupler

1700-2300 MHz

P/N: FLT53C1723D-5070A

*Contents in this sheet are subject to change without prior notice.

LTCC Coupler 5031 Size, For 1700-2300 MHz Working Frequency


1. Features

High Isolation and Low Insertion Loss.

2. Applications

Applications using GSM, UMTS, and LTE.

3. Shapes & Dimensions



Mark	L	W	T	a	b	c
Dimensions (mm)	5.08±0.25	3.18±0.25	1.4±0.10	0.38±0.10	0.76±0.15	0.60±0.15


4. Terminal Pin Definition

	①	②	③	④
Case1	Input	Isolated	Direct	Coupled
Case2	Isolated	Input	Coupled	Direct
Case3	Direct	Coupled	Input	Isolated
Case4	Coupled	Direct	Isolated	Input


5. Electrical Characteristics

Pass Band (MHz)	Insertion Loss (dB)	VSWR	Isolation (dB)
1700-2300	0.19 typ. 0.35 max.	1.30 max. (1.19 typ.) @ 1700-2300 MHz 1.30 max. (1.15 typ.) @ 1805-1880 MHz 1.20 max. (1.11 typ.) @ 1930-1990 MHz 1.20 max. (1.07 typ.) @ 2110-2200 MHz	17 min. (19 typ.) @ 1700-2300 MHz 17 min. (20 typ.) @ 1805-1880 MHz 20 min. (21 typ.) @ 1930-1990 MHz 20 min. (23 typ.) @ 2110-2200 MHz
Coupling (dB)	2.40-3.30 @ 1700-2300 MHz		
Phase Balance (Deg)	90±5 @ 1700-2300 MHz		
Impedance	50 Ω		
Power Capacity	25 W Avg.		
MSL	LEVEL 1		
Operating and Storage Condition Operation Temperature Range: -55 ~ +125℃ Storage Temperature Range: -55 ~ +125℃		Storage Condition before Soldering Storage Temperature Range: +10 ~ +30℃ Humidity: 30 to 70% relative humidity	

6. Typical Electrical Performance at T= 25±5°C




7. Recommended PCB Layout




* Line width should be designed to match 50Ω characteristic impedance, depending on PCB material and thickness.

8. Reflow Soldering Standard Condition



9. Packaging and Dimensions 5031

◆ Plastic Tape




A_0	B_0	W	F	E	P_0	P_1	P_2	D_0	K_0	T	$10 P_0$
3.50 ± 0.10	5.40 ± 0.10	12.0 ± 0.30	5.50 ± 0.10	1.75 ± 0.10	4.00 ± 0.10	8.00 ± 0.10	2.00 ± 0.10	1.50 ± 0.10	1.55 ± 0.10	0.25 ± 0.02	40.00 ± 0.20

◆ Ordering Code

F	LT	53	C	1723	D	5070A
FTR device	LTCC Technology	Size: 5031	Coupler	Working Frequency: 1700-2300 MHz	Terminal electrode	Design code

◆ **Remarks for Package**

Reserve a length of $\geq 150\text{mm}$ for the trailer of the carrier and $\geq 150\text{mm}$ for the leader of the carrier and further $\geq 150\text{mm}$ of cover tape at the leading part of the carrier.

◆ **Reel (1000 pcs/Reel)**◆ **Storage Period**

Product should be used within 12 months from the day of FTR outgoing inspection.

Storage Temperature Range : $+10 \sim +30$ degree C, Humidity : 30~70% RH.

10. Reliability Test

Test item	Test condition / Test method	Specification
Solderability IEC 60068-2-58 GB/T2423.28	*Solder bath temperature: 240±5°C *Immersion time: 2±0.5 sec Solder: Sn96.5 Ag3.0 Cu0.5 for lead-free.	At least 95% of a surface of each terminal electrode must be covered by fresh solder.
Leaching (Resistance to dissolution of metallization) JIS C5101	*Solder bath temperature: 260±5°C *Leaching immersion time: 10±1 sec Solder: Sn96.5 Ag3.0 Cu0.5 for lead-free.	Loss of metallization on the edges of each electrode shall not exceed 25%.
Resistance to soldering heat IEC 60068-2-58 GB/T2423.28	*Preheating temperature: 120~150°C, 1 minute. *Solder temperature: 260±5°C *Immersion time: 10±1 sec Solder: Sn96.5 Ag3.0 Cu0.5 for lead-free Measurement to be made after keeping at room temperature for 24±2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature. Loss of metallization on the edges of each electrode shall not exceed 25%.
Drop Test IEC 60068-2-32 GB/T2423.8 Customer's specification.	*Height: 50 cm *Test Surface: Rigid surface of concrete or steel. *Times: 6 surfaces for each units; 2 times for each side.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
Vibration IEC 60068-2-6 GB/T 2423.10	*Frequency: 10Hz~55Hz~10Hz(1min) *Total amplitude: 1.5mm *Test times: 6hrs.(Two hrs each in three mutually perpendicular directions)	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
Adhesive Strength of Termination IEC60068-2-21 GB/T 2423.60	*Pressurizing force: LGA terminal series : 2N(0605); 3N(1005); 5N(≥1608) DIP terminal series : 3N(1005); 5N(1608); 10N(≥2012) *Test time:10±1 sec	No remarkable damage or removal of the termination.

Bending test IEC 60068-2-21 GB/T 2423.60	The middle part of substrate shall be pressurized by means of the pressurizing rod at a rate of about 1 mm/s per second until the deflection becomes 2mm and then pressure shall be maintained for 10±1 sec. Measurement to be made after keeping at room temperature for 24±2 hours.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
Temperature cycle IEC60068-2-14 GB/T 2423.22	30 minutes at -55°C±2°C. 10~15 minutes at room temperature. 30minutes at +125°C±2°C. 10~15 minutes at room temperature. Total 100 continuous cycles Measurement to be made after keeping at room temperature for 24±2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
High temperature IEC 60068-2-2 GB/T2423.2	*Temperature: 125±2°C. *Test duration: 500+24/-0 hours. Measurement to be made after keeping at room temperature for 24±2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics.
Humidity (steady conditions) IEC60068-2-3 GB/T 2423.3	*Humidity: 85±5%R.H. *Temperature: 85±2°C. *Time: 500+24/-0 hrs. Measurement to be made after keeping at room temperature for 24±2 hrs ※ 200hrs measuring the first data then 300hrs data.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.
Low temperature IEC 60068-2-1 GB/T2423.1	*Temperature: -55±2°C. *Test duration: 500+24/-0 hours Measurement to be made after keeping at room temperature for 24±2 hrs.	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics at the room temperature.